

# washers



## COIN-OPERATED Washer-Extractors

20 lb (9 kg)  
25 lb (11 kg)  
30 lb (14 kg)  
40 lb (18 kg)  
60 lb (27 kg)  
80 lb (36 kg)

Washer-Extractor  
Washer-Extractor  
Washer-Extractor  
Washer-Extractor  
Washer-Extractor

# Speed Queen®

### Heavy Duty Construction

Durable 304 stainless steel cabinet front, sides and top, as well as inner and outer tubs, won't corrode, chip, crack or pit with normal use, and they're extremely rust resistant. Our



heavy-duty Gamma A-Frame stands up to even the toughest

laundry conditions, keeping Speed Queen washer-extractors durable for years to come.

### Large Door Opening

Large door opening makes loading and unloading fast and easy. Our



heavy-duty stainless steel door features vacuum tight sealing to keep water inside the machine where it belongs. The door lock, as well as the heat-treated, shatter-proof circular door glass, helps operators to safely view the wash process.

### Superior Serviceability

Speed Queen's removable top and front panels are designed for minimum down time and ease of service. Now troubleshooting electrical systems as well as accessing drain valve components is easier than ever.



### Reversing Wash Action

The alternate rotating wash action includes a wash and three full rinses. It thoroughly cleans your customers clothes without damaging those delicate fabrics.

### Low Water Usage

Speed Queen washer-extractors are designed to save water and energy. This translates into operational efficiency, satisfied customers, and more importantly, bottom line profits.

### Heavy-Duty Bearings and Trunion Assembly

Sealed heavy-duty bearings require no lubrication — permanently!



# Washer-Extractor Specifications

	SC20	SC25	SC30	SC40	SC60	SC80
<b>Capacity</b>	20 lb (9 kg)	25 lb (11 kg)	30 lb (14 kg)	40 lb (18 kg)	60 lb (27 kg)	80 lb (36 kg)
<b>Width (in/mm)</b>	26" (660 mm)	26" (660 mm)	29" (737 mm)	30 5/8" (778 mm)	34 1/16" (865 mm)	41 1/2" (1054 mm)
<b>Depth (in/mm)</b>	29 11/16" (754 mm)	33 11/16" (856 mm)	35" (889 mm)	40 1/4" (1022 mm)	42 4/5" (1086 mm)	51 5/8" (1311 mm)
<b>Height (in/mm)</b>	42" (1067 mm)	45" (1143 mm)	45" (1143 mm)	47 1/4" (1200 mm)	50" (1269 mm)	56" (1422 mm)
<b>Cylinder Diameter (in/mm)</b>	21" (533 mm)	21" (533 mm)	24" (610 mm)	26 1/4" (667 mm)	30" (762 mm)	36" (914 mm)
<b>Cylinder Volume</b>	2.76 cu. ft. (78.1 liters)	3.76 cu. ft. (106 liters)	4.19 cu. ft. (118 liters)	6.34 cu. ft. (180 liters)	9.0 cu. ft. (255 liters)	12.96 cu. ft. (367 liters)
<b>Door Opening Size (in/mm)</b>	12" (305 mm)	12" (305 mm)	14 11/32" (364 mm)	16 1/4" (413 mm)	16 1/4" (413 mm)	18 1/2" (470 mm)
<b>Door Bottom to Floor (in/mm)</b>	14 3/8" (366 mm)	14 3/8" (366 mm)	14" (356 mm)	14 1/2" (368 mm)	13 1/2" (343 mm)	17 3/4" (451 mm)
<b>Door Factor (High Extract)</b>	82	87	78	82	86	85/140
<b>Wash Speed (rpm)</b>	53	55	47	47	44	22/40
<b>High Extract (rpm)</b>	525	540	480	470	450	280/408/524
<b>Water Inlet Conn. (in/mm)</b>	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)
<b>Drain Diameter (in/mm)</b>	2.375" (60 mm)	2.375" (60 mm)	2.375" (60 mm)	3" (76 mm)	3" (76 mm)	3" (76 mm)
<b>Drain Height to Floor (in/mm)</b>	4 3/8" (111 mm)	4 3/8" (111 mm)	4" (102 mm)	4 3/4" (121 mm)	3 1/2" (89 mm)	5 3/4" (146 mm)
<b>Motor HP (wash)</b>	.18 HP (.13 kW)	.25 HP (.19 kW)	.25 HP (.19 kW)	.40 HP (.30 kW)	.55 HP (.41 kW)	N/A
<b>Motor HP (extract)</b>	1.0 HP (.75 kW)	1.4 HP (1.04 kW)	1.4 HP (1.04 kW)	1.8 HP (1.3 kW)	2.7 HP (2.01 kW)	5 HP (3.7 kW)
<b>Voltage/Hz/Phase*</b>	220-240/50/1	220-240/50/1	220-240/50/1	380-415/50/3	380-415/50/3	380-415/50-60/3
<b>Circuit Breaker-FLA</b>	20-10 amp	20-10 amp	20-10 amp	15-5 amp	15-6 amp	15-4.5 amp
<b>Shipping Dimensions (in/mm)</b>	H: 51" (1295 mm) W: 29" (737 mm)	H: 53 1/2" (1359 mm) W: 29" (737 mm)	H: 53 1/2" (1359 mm) W: 30 1/2" (775 mm)	H: 56" (1422 mm) W: 32" (813 mm)	H: 58 1/2" (1486 mm) W: 36" (914 mm)	H: 62 1/2" (1588 mm) W: 48" (1219 mm)
<b>Net Weight</b>	D: 32 1/2" (826 mm) 390 lb (177 kg)	D: 36 1/4" (921 mm) 435 lb (198 kg)	D: 37 1/2" (953 mm) 495 lb (225 kg)	D: 41" (1041 mm) 706 lb (321 kg)	D: 44 1/2" (1130 mm) 826 lb (375 kg)	D: 56" (1422 mm) 1406 lb (639 kg)
<b>Standard Shipping Weight</b>	410 lb (186 kg)	470 lb (214 kg)	535 lb (243 kg)	744 lb (338 kg)	881 lb (400 kg)	1456 lb (662 kg)
<b>Wood Crate Shipping Weight</b>	480 lb (218 kg)	530 lb (241 kg)	601 lb (273 kg)	846 lb (385 kg)	1020 lb (464 kg)	1506 lb (685 kg)
<b>Agency Approvals</b>	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc


\* Standard domestic voltage 208-240/60/3. Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines. All CE approved models available in 50 hz 20-60 models.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification. Features and certifications may vary by model. Agency approvals may vary depending on configuration. Consult factory for details.

©Copyright 2003 Alliance Laundry Systems LLC

## Activation Options

The world drop comes pre-programmed to accept coins for your market. Additional coins or a metallic token can be added by the owner by using a unique and simple "Teach Mode".



World Drop

## Control Options



Electromechanical Timer Control

Speed Queen offers four preset wash formulas to get clothes their cleanest while maximizing efficiency. Customers can choose from a variety of wash cycles such as hot for heavy soils and whites; warm for medium soils and permanent press, and cold for all cold water wash, delicates, knits, and lightly soiled fabrics.

As an added convenience, we've incorporated a cycle indicator to keep your customer informed of wash cycle status. This way the customer can determine which wash or rinse step the machine is in. A separate light also informs the customer when to add bleach so there's no question about it.



Fully Programmable B-Micro Control

The B-Micro control is designed to offer you eight pre-programmed cycles. These cycles can be customized to fit your specific needs. By customizing your cycles you can significantly reduce water consumption. Turnaround time is also improved by doing the maximum amount of cleaning in the smallest amount of time. The B-Micro is also very easy to operate with a separate start pad and cycle symbols designed to match garment care labels.



Ph: 1800 30 40 30



www.andrewbarton.com.au